



Shanghai Huishi Package Material Co.,Ltd.

HS-1015


Double Sided PE Foam Tape

Technical Data

August, 2017

Product Description PE foam tape combine a conformable PE foam with a high strength acrylic adhesive that provides good initial tack and offers high ultimate adhesion to a wide variety of surfaces.

Product Construction	Carrier	Adhesive	Total Tape Thickness W/O Liner	Tape Color	Liner
	PE foam	Acrylic adhesive	1.5mm	Black/white	Red/green/blue PE film



Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purpose

		Test Method
Initial adhesion	≧ 24#	GB/T 4852-2002
Adhesion to Steel:	≧ 20N/25mm	GB/T 2792 -2014
Holding power:	≧ 24H	GB/T 4851-2014
Density	67kg/m ³	
Backing Thickness:	1.5mm	GB/T 7125-2014
Total Thickness(W/O liner):	1.6mm (+-0.1mm)	GB/T 7125-2014
Temperature Use Range:	Up to 176 °F (80 °C)	

Features

- Good initial tack
- Offers high ultimate adhesion, permanent bonding
- Flexibility, conforms cleanly to both smooth and irregular surfaces
- Easily die cut
- Available in various thickness and colors
- High shear strength gives high load bearing ability

-
- | | |
|--------------------------|---|
| Application Ideas | <ul style="list-style-type: none">• For many joining, mounting, gasketing and sealing applications involving irregular surfaces.• Mounting of indoor/outdoor signs and nameplates in display exhibition industry• For plastic hooks, racks and dispensers• Gasketing, cushioning, anti vibration in vehicles, electronics• Filling and sealing gaps around windows, doors, and car/SUV tops |
|--------------------------|---|
-

Storage	Store under normal conditions (25 °C ± 2 °C) * (65% ± 5% RH) avoid direct sunlight in the original packaging material
----------------	---

Shelf Life	To obtain best performance, use this product within 12 months from date of manufacture.
-------------------	---

Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that we believes are reliable, but the accuracy or completeness of such information is not guaranteed.
------------------------------	--

Product Use	Many factors beyond HS's control and uniquely within user's knowledge and control can affect the use and performance of a HS product in a particular application. Given the variety of factors that can affect the use and performance of a HS product, user is solely responsible for evaluating the HS product and determining whether it is fit for a particular purpose and suitable for user's method or application.
--------------------	--

Limitation of Liability	Except where prohibited by law, HS will not be liable for any loss or damage arising from the HS product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability
--------------------------------	---

This Industrial Adhesives and Tapes was manufactured under a quality system registered to ISO 9001:2015 standards.

HS holding
Shanghai Huishi Package Material Co.,Ltd.

5 Floor, Building B1 ,No. 161 ,Zhenye Road, Dongjing Town,

Songjiang District, 201619 Shanghai, China.

Tel: +86 021 67690018

Fax: +86 021 67690873

Web: www.chinahstape.com